

EP749 Projector

Small in Size...Big in Features

Optoma's EP749 is a lightweight, multimedia data projector that features DLP® technology, native XGA resolution and 2500 lumens of brightness. Weighing only 4.4 pounds, the portable EP749 is HDTV compatible and has a number of connectivity options for multiple video sources. The Optoma EP749 offers a sturdy, well-built solution for environments that demand crisp image quality.



Features

- True XGA (1024 x 768) resolution with SXGA+ compression
- 2500 lumens rating with 2200:1 contrast ratio
- HDTV compatible (720p, 1080i)
- Convenient DVI-D w/HDCP, component, composite, and s-video inputs
- Adjustable cooling fan speed settings for higher altitudes
- Weighs 4.4 pounds

Specifications

Brightness

2500 ANSI Lumens

Resolution

Native XGA (1024 x 768)

Contrast Ratio

2200:1

Lamp Life and Type

2000/3000 Hours (STD/ECO)
230W SHP

Display Type

Single 0.55" DDR DMD™ DLP®
Technology by Texas Instruments

Throw Ratio

1.93-2.13:1 (Distance/Width)

Projection Distance

4.8' to 39.4' (1.5 to 12 m)

Image Size

34.67" to 305" (0.9 to 7.7 m)

Aspect Ratio

Native 4:3, 5:4 & 16:9 Compatible

Horizontal Scan Rate

31.5 to 80 kHz

Vertical Refresh Rate

56 to 85 Hz

Keystone Correction

± 16° Vertical

Audio

One Internal 2-Watt Speaker

Displayable Colors

16.7 Million, 256 Shades of Gray

Uniformity

85%

Remote Control

Fully Featured Remote with Laser Pointer

Computer Compatibility

XGA, SVGA, VGA, SXGA+ Resized, VESA,
PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, EDTV (480p),
HDTV (576i/p, 720p, 1080i)

Monitor Loop Through

D-Sub 15-pin VGA Output (Functional in
Both Normal and Standby Modes)

Projection Lens

F=2.35~2.47, f=21.83~23.81 mm,
1.1x Manual Zoom and Focus

User Controls

Advanced Adjustability Options through
the On-Screen Display

I/O Connection Ports

DVI-D w/HDCP, VGA, S-Video,
Composite Video, Audio Mini-Jack,
RS-232, VGA-Out

Projection Method

Front, Rear, Table Top and Ceiling Mount

Weight

4.4 lbs (2 kg)

Dimensions (W x H x D)

9.3" x 3.8" x 8.2" (238 x 96 x 210mm)

Operating Temperature

5 to 35°C, 80% Max Humidity

Storage Temperature

-20 to 60°C, 80% Max Humidity

Noise Level

33dB/28dB (ECO/STD)

Power Supply and Consumption

100-240 Volts, 50-60Hz
190W, <10W Standby Power

Standard Accessories

AC Power Cord, VGA-VGA Cable,
RS-232 Cable, Composite Video
Cable, Remote Control, Batteries for
Remote, CD-ROM User's Manual,
Quick Start Guide, Warranty Card,
Lens Cap and Carrying Case

Optional Accessories

Ceiling Mount, 15-pin to 3 RCA
Component-HDTV Adapter, DVI to
HDMI Adapter, S-Video Cable,
GrayWolfII™ Series Screens and
Gold Service Warranty

Warranty

1 Year Limited Parts and Labor,
90 Days Lamp

UPC

796435 11 315 5